

# YAK 112 / 112C

## PNEUMATIC JACKS



**YAK**

# YAK 112 / 112C

## PNEUMATIC JACKS

### PNEUMATIC JACKS

Pneumatically controlled jacks consisting of a highly resistant diaphragm and internal telescopic guide. The jacks are fitted with a stop limit device as well as a safety valve, making them absolutely reliable in the case of excessive loads. Silent, simple and lightweight - they are ideal for tyre repairers and bodywork shops. They can also be used on column lifts. Also available in a trolley version (C).

### TECHNICAL DATA

	112	112C
Capacity	2 t / 2.2 ton	2 t / 2.2 ton
Net weight	16.5 kg / 36 lb	16.5 kg / 36 lb
Working air pressure	8-10 bar / 116-145 psi	8-10 bar / 116-145 psi
Air consumption	100 nl / min	100 nl / min
Max stroke	228mm	228mm
Min. height	112mm	112mm
Number of pistons	2	2
Pistons stroke	97 – 97 mm / 3.8 – 3.8 in	97 – 97 mm / 3.8 – 3.8 in

### DIMENSIONS

	112		112C	
	mm / t	in / ton	mm / t	in / ton
A	-	-	1109	43.66
B	492	19.37	492	19.37
C	250	9.84	250	9.84
D	112-340	4.41-13.39	112-340	4.41-13.39

