

YAK 132 / 132C

PNEUMATIC JACKS



YAK 132 / 132C

PNEUMATIC JACKS

PNEUMATIC JACKS

Pneumatically controlled jacks consisting of a highly resistant diaphragm and internal telescopic guide. The jacks are fitted with a stop limit device as well as a safety valve, making them absolutely reliable in the case of excessive loads. Silent, simple and lightweight - they are ideal for tyre repairers and bodywork shops. They can also be used on column lifts. Also available in a trolley version (C).

TECHNICAL DATA

	132	132/C
Capacity	2 t / 2.2 ton	2 t / 2.2 ton
Net weight	14 kg / 31 lb	17 kg / 37lb
Working air pressure	8-10 bar / 116-145 psi	8-10 bar / 116-145 psi
Air consumption	100 nl / min	100 nl / min
Max stroke	194 mm / 7.6 in	194 mm / 7.6 in
Min. height	132 mm / 5.2 in	132 mm / 5.2 in
Number of pistons	2	2
Pistons stroke	97 – 97 mm / 3.8 – 3.8 in	97 – 97 mm / 3.8 – 3.8 in

DIMENSIONS

	132		132/C	
	mm / t	in / ton	mm / t	in / ton
A	-	-	1070	42.13
B	415	16.34	365	14.37
C	250	9.84	250	9.84
D	132-326	5.2-12.83	132-326	5.2-12.83

