

YAK 203 / 203C

PNEUMATIC JACKS



YAK 203 / 203C

PNEUMATIC JACKS

PNEUMATIC JACKS

Pneumatically controlled jacks consisting of a highly resistant diaphragm and internal telescopic guide. The jacks are fitted with a stop limit device as well as a safety valve, making them absolutely reliable in the case of excessive loads. Silent, simple and lightweight - they are ideal for tyre repairers and bodywork shops. They can also be used on column lifts. Also available in a trolley version (C).

TECHNICAL DATA

	203	203/C
Capacity	2 t / 2.2 ton	2 t / 2.2 ton
Net weight	17 kg / 37 lb	20 kg / 44 lb
Working air pressure	8-10 bar / 116-145 psi	8-10 bar / 116-145 psi
Air consumption	100 nl / min	100 nl / min
Max stroke	285 mm / 8.1 in	285 mm / 11.2 in
Min. height	205 mm / 8.1 in	205 mm / 8.1 in
Number of pistons	3	3
Pistons stroke	95 – 95 – 95 mm / 3.7 – 3.7 – 3.7 in	95 – 95 – 95 mm / 3.7 – 3.7 – 3.7 in

DIMENSIONS

	203		203/C	
	mm / t	in / ton	mm / t	in / ton
A	-	-	1070	42.13
B	415	14.34	365	14.37
C	250	9.84	250	9.84
D	205-490	8.07-19.29	205-490	8.07-19.29

